

CONSTRUCTION GROUT

ITEM/DESCRIPTION	PACKAGING
MasterFlow 928 - A high precision, nonshrink, natural aggregate grout with extended working time. Recommended for precision nonshrink grouting of machinery and equipment, baseplates and soleplates; grouting anchor bolts, reinforcing bars and dowel rods; applications requiring grout to be pumped; marine applications; freeze/thaw environments.	55# Bags (60 Bags/Pallet)
MasterFlow 100 (Construction Grout MB) Yields .40 cubic feet/50# bag	50# Bag (60 Bags/Pallet)
NEW! MasterFlow 555 - A semi-fluid, non-shrink mineral-aggregate grout. Ideally suited for grouting machines or plates requiring optimum load bearing support.	50# Bags (60 Bags/Pallet)
MasterFlow 885 (Embeco 885) - A high precision, nonshrink metallic aggregate grout with extended working time. Recommended for precision nonshrink grout of machinery and equipment; grouting anchor bolts, reinforcing bars and dowel rods.	55# Bags (60 Bags/Pallet)
Masterflow 648 (MasterFlow 648 CP Plus) - An epoxy grout that combines high temperature performance and crack resistance with outstanding flow characteristics and versatility of fill rates. High early and seven day strengths. Good chemical resistance. Coverage is 1.73 cubic feet. "Low Dust"	
MasterEmaco T430 (Emaco T430) - This one-component product can be placed into service in as little as six hours for standard rubber tire traffic. EMACO T430 repair mortar offers versatile, durable repairs that can be rapidly returned to service. It is specially suited for hot weather applications when extended working time is required. Easy to use; just add water and mix.	55# Bags (60 Bags/Pallet)
MasterEmaco T545 (Set 45 Regular) & MasterEmaco T545 HT (Master-Emaco Hot Weather) - A one-component concrete repair and anchoring material which set in 45 minutes and takes rubber tire traffic 45 minutes after placement. This product bonds to both concrete and masonry and can be used indoors and outdoors for a variety of highway and heavy industrial repair jobs. Regardless of the temperature, SET 45 HOT WEATHER formula with aggregate should be used for deep placements. Easy to use - just add water.	50# Bags (60 Bags/Pallet) Regular
	Hot Weather
MasterEmaco T 310 CL (Emaco R310 CI) - Repair mortar/polymer-modified cement based mortar with an integral corrosion inhibitor. Used for patching or resurfacing distressed horizontal concrete surfaces.	55# Bags (60 Bags/Pallet)
MasterEmaco N 423 RS (Emaco FS) - A fast setting concrete repair compound for horizontal, vertical and overhead use. It molds easily, and can be formed and shaved readily before final set.	50# Bags

Carried In Stock

Carried In Stock

Carried In Stock

There are many other Master Builders items available on a special order basis - Call office for details.



www.BASFBuildingSystems.com

www.fivestarproducts.com

CONCRETE
REPAIR PRODUCTS

NON-SHRINK GROUTS

Non-shrink, non-corrosive, high-strength grouts for a variety of applications including:

Setting large machinery • Setting structural columns • Anchoring bolts • Placement of bearing plates • Power line stanchions

ITEM	PACKAGING
5-Star Grout (Standard) - Yields 1/2 cubic foot/50# bag.	50# Bag (56 Bags/Pallet)

Carried In Stock

ITEM/DESCRIPTION	PACKAGING
MasterEmaco N 424 (Emaco GP) - Patching mortar with a short 20 minute set time.	50# Bags (56 Bags/Pallet) 60# Pail (36 Pails/Pallet)
MasterEmaco T 1060 (10-60 Rapid Mortar) - One component, very rapid setting cement-based mortar. Designed for horizontal concrete surfaces where high early strength is required.	50# Bags (60 Bags/Pallet)
MasterEmaco T 1061 (10-61 Rapid Mortar) - One component shrinkage-compensated cement-based mortar with an extended working time. Designed for repairing horizontal concrete surfaces.	50# Bags (60 Bags/Pallet)
MasterFlow 110AN (Sonopost) - A rapid setting anchoring material for setting post and columns.	5 Gallon Pails (36 Pails/Pallet)

There are many other Master Builder and 5-Star items available on a special order basis. Call office for details.